

Brown Pine Tar

Classic wood tar matt brown color

General

Brown Pine Tar is a classic pigmented pine tar based on genuine tar, gum turpentine and linseed oil which gives the surface a dull brown color. Brown Pine Tar gives a rejected water surface and protection against UV-radiation. Contains 100% active ingredients.

Pine Tar is nature's own wood protection and consists among others various kinds of resins and terpenes. Resins are the tree's natural way of protecting themselves against micro-organisms and heal injuries. Terpenes are a solvent and it accelerates the drying process. Pine Tar is produced of resin-rich pine trees in furnace.

Range of application

Brown Pine Tar can be used on wood that has been previously treated with earth paint (as Falu Red) and copperas, and also on untreated or previously tarred wood paneling, timber such as facades, fences, wooden ceilings, pallet collars etc.

Packaging

60530401 / 1-lit can
60530473 / 3-lit can
60530556 / 10-lit can

Instructions for use

For best result apply **Brown Pine Tar** in warm weather, at least 10 degrees Celsius. The product becomes then easier to work with and it penetrates right into the timber. **Brown Pine Tar** should be mixed with at least 20% gum turpentine. For easier penetration of planned wood such as timber facades, **Brown Pine Tar** should be further diluted with 10-15% gum turpentine.

As pigment settles during storage, it is important to thoroughly stir the can before painting. Stir although occasionally during painting.

Be aware of that **Brown Pine Tar** is a product of nature where the appearance may vary from different batches. If you have several cans of various productions (see white label on the cover), you should mix these together to avoid color differences.

Brown Pine Tar shall not be withdrawn on wood previously treated with other solid colors

Painting:

Brush to remove dust, dirt and loose paint. Wash off algae and mold growth. The surface must be dry before painting. Paint directly without primer. Use a brush. You can also spray, dilute then by 10-20% gum turpentine, depending on the used spray equipment. Recoat after about 1-2 days. Paint 2 times for optimal protection and the best color.

Ensure good ventilation. Painting outdoors. Material Safety Data Sheet will be found at www.auson.se and painting instructions at www.tjarlek.se.

Technical data

Color:	Brown (dull)
Density:	1,11± 0,03 kg/lit
Weight solids:	80%
Coverage:	5-8 m ² /lit depending on surface
Drying time:	From several days to several weeks, depending on weather, planed or unplanned lumber, wood, thickness and how well the tar has seeped into the ground.
Dilution:	Gum turpentine, NB! No white spirit
Cleaning:	Gum turpentine, alcohol or soap/water
Storage:	36 months (unopened can)

For further information we recommend the safety data sheet or instruction on package.

Issue:: 2016-12-30 / AA



Auson AB, Kungsbacka, Sweden
T: +46 (0)300-56 20 00
www.auson.se

These information are for guidance only and are given without obligation. If there is some confusion we recommend that you do your own tests and ask for advice in writing from us.